

E220 Print Cartridge

Printer: E220

Declaration of Yield:	Average Cartridge Yield	2500	standard pages
Declared yield value in accordance with ISO/IEC 19752			

Average 3409
Std Dev 223
90% Lower Confidence 3293

For questions concerning testing contact:

Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

	<u>start</u>	<u>stop</u>
Date tested	19-Nov-2004	21-Nov-2004
Number of cartridges in testing		12
Qty. of cartridges used in calculation		12
Shake Procedure	1st shake	At fade
	2nd shake	At fade
Print mode		Continuous
Number of printers tested		5
Media used		Boise Cascade X-9 - 20# - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		8.6
Operating system		Windows 2000
Application software		Adobe Acrobat version 6.01
Test page version		IS_19752_Testpage_Ver.200406.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
CAD041595223	NOCATV40	74	75	74	48	49	48	3,461	Y
CAD041603191	890943X	74	75	74	48	49	48	3,665	Y
CAD041613245	8919H7R	74	75	74	48	49	48	3,418	Y
CAD041620212	8919PN4	74	75	74	48	49	48	3,188	Y
CAD041620221	NOCATV40	74	74	74	48	48	48	3,088	Y
CAD041595082	890943X	74	74	74	48	48	48	3,289	Y
CAD041604331	8919H7R	74	74	74	48	48	48	3,327	Y
CAD041611697	8918PN4	74	74	74	48	48	48	3,219	Y
CAD041611382	NOCATV40	74	75	74	48	49	48	3,899	Y
CAD041620188	890943X	74	75	74	48	49	48	3,571	Y
CAD041595796	8919H7R	74	75	74	48	49	48	3,356	Y
CAD041604312	8918PN4	74	75	74	48	49	48	3,428	Y

Comments and or exceptions: