

W820 Print Cartridge

Printer: W820

Declaration of Yield:

Average Cartridge Yield 30000 standard pages Declared yield value in accordance with ISO/IEC 19752

Average 33007
Std Dev 833
90% Lower
Confidence 32490

For questions concerning testing contact:
Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

Date tested start stop
8-Jun-2005 15-Jun-2005

Number of cartridges in testing	9	
Qty. of cartridges used in calculation	9	
Shake Procedure	1st shake	At toner low
	2nd shake	At toner low
Print mode		Continuous
Number of printers tested		3
Media used		Boise Cascade X-9 - 20# - Letter
Paper feed orientation		Long Edge Feed (LEF)
Driver version		W820 Driver Version 7.4.2
Operating system		Windows XP SP2
Application software		Adobe Acrobat Version 6.0.2
Test page version		IS_19752_Testpage.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
J0-40800-5412K30-CT350006	152970	74	75	73	55	60	53	33,290	Y
J0-41023-5408K30-CT350006	165579	74	75	73	55	60	53	32,840	Y
J0-41381-5411K30-CT350006	165601	74	75	73	55	60	53	33,640	Y
J0-41024-5408K30-CT350006	152970	75	75	74	55	60	52	32,560	Y
J0-41028-5408K30-CT350006	165579	75	75	74	55	60	52	34,180	Y
J0-41027-5408K30-CT350006	165601	75	75	74	55	60	52	33,000	Y
J0-40811-5412K30-CT350006	152970	76	77	74	53	60	47	31,320	Y
J0-41018-5408K30-CT350006	165579	76	77	74	53	60	47	32,570	Y
J0-41011-5408K30-CT350006	165601	76	77	74	53	60	47	33,660	Y

Comments and or exceptions: