



# Lexmark CX951se

Versatile. Simple. Sustainable.













#### Lexmark CX951se

With the new CX951se colour A3 multifunction printer, you get reassuring versatility, exceptional sustainability, and surprising simplicity from such sophisticated technology. Boost your productivity with vivid prints - up to 35 pages per minute\*. Intuitively navigate the 25 cm colour touchscreen, and save time with single-pass two-sided scanning. Effortlessly create everything your business requires, and custom configure your multifunction printer with interchangeable options tailored to your needs.

## Versatile: Easy to Use

Create everything your business requires and anything you can imagine - from standard office documents to marketing brochures, booklets and posters - with broad media size support, high-volume printing, and exceptional paper handling and finishing capabilities.

**Print vivid, colourful visualisations, charts and documents** with professional colour features (including PANTONE® calibration) and a full range of media sizes so you can effectively communicate your ideas.

**Easily incorporate your multifunction printer into your workspace** with a versatile, configurable design that saves space without sacrificing performance.

**Boost your productivity** with our rich suite of cutting-edge software and solutions with broad capabilities including scanning paper files directly into your cloud-based storage systems and automatically translating documents into 100+languages.

**Further your organisation's digital transformation** with direct integration into your critical workflows and core business systems using these IoT-enabled devices.



## Simple: Easy to Manage

**Quickly do what you need to do** using an intuitive operator panel and easy-to-follow navigation.

**Easily maintain your devices** with one-handed toner replacement, easy-to-reach serviceable areas, and alerts that are simple to understand.

**Enjoy the peace of mind of knowing you are protected** by the industry's most comprehensive security portfolio, right out of the box.

**Keep your business running** with exceptional reliability, industry-leading durability, and long-lasting toner and supplies.

Rest easy that every aspect of your device is made to work together seamlessly thanks to Lexmark's core technology ownership.

# Sustainable: Easy to feel good about

Feel good about your purchase and help meet your own sustainability goals with our world-class practices and independent third-party certifications.

**Do your part for the planet** with our industry-leading use of post-consumer recycled materials.

**Save energy - and money -** with technology that exceeds strict global standards for energy efficiency.


**Minimise your impact on the environment** with a company that focuses on sustainability throughout the product lifecycle from design through use, end of life and beyond.

This is a Class A device according to international electromagnetic emissions standards (i.e. FCC Rules, EN 55022/EN 55032, etc.). Class A products are intended for use in non-residential/non-domestic environments. Use of a Class A product in residential/domestic environments may cause interference to radio communications and require corrective measures.

<sup>\*</sup> Print speeds measured in accordance with ISO/IEC 24734 (ESAT). For more information see: www.lexmark.com/ISOspeeds.

<sup>\*\*</sup> Fax icon shown on the operator panel when Fax Server is enabled, Fax Over IP is configured, etherFAX is configured, or an optional Analog Modem is installed.

#### Lexmark CX951se



- Dimensions included as part of base model
- 3 150-Sheet multipurpose feeder Dimensions included as part of base model
- 4 550-Sheet tray Dimensions included as part of base model
- 550-Sheet Tray 5 163 x 587 x 649 mm
- 2 x 550-Sheet Tray 6 314 x 587 x 649 mm
- 7 2000-Sheet Tandem Tray - A4 314 x 587 x 649 mm
- 8 Cabinet 247 x 587 x 660 mm
- 9 1500-Sheet High-Capacity Tray 290 x 342 x 545 mm

| 11 | 184 x 612 x 555 mm   | 7 |
|----|--|---|
| 12 | 500-Sheet Staple Finisher<br>150 x 546 x 523 mm                            | 7 |
| 13 | Offset Stacker<br>107 x 420 x 489 mm                                       | 7 |
| 14 | 1250-Sheet Staple 2/4 Hole Punch<br>Finisher<br>995 x 575 x 610 mm         | 7 |
| 15 | 2250-Sheet Booklet Staple 2/4 Hole<br>Punch Finisher<br>995 x 650 x 613 mm | 7 |
|    | Standard   | 7 |

Lexmark CX950, 951, 833, XC9525, 9535, 8355 Black 47.7K Toner Cartridge Lexmark CX950, 951, 833, XC9525, 9535, 8355 Cyan 46.9K Toner Cartridge Lexmark CX950, 951, 833, XC9525, 9535, 8355 Magenta 46.9K Toner Cartridge Lexmark CX950, 951, 833, 79I 0H40 XC9525, 9535, 8355 Yellow 46.9K Toner Cartridge 79L3HC0 Lexmark CX950, 951, 833 Cyan Return Programme 46.9K Toner 79L3HK0 Lexmark CX950, 951, 833 Black Return Programme 47.7K Toner Cartridge Lexmark CX950, 951, 833 79L3HM0 Magenta Return Programme 46.9K Toner Cartridge Lexmark CX950, 951, 833 Yellow 79L3HY0 Return Programme 46.9K Toner Cartridge Optional P/N **Paper Handling** 20L8800 550-Sheet Tray

201 8801

20L8802

20L8803

20L8804

201 8810

20L8811

20L8812

20L8813

2018814

20L8815

20L8816

20L8817

2 x 550-Sheet Tray

Punch Finisher

**Punch Finisher** 

Offset Stacker

Hole Punch Finisher

Hole Punch Finisher

Paper Transport Unit

Letter

2,000-Sheet Tandem Tray - A4

1,500-Sheet High-Capacity Tray

2,000-Sheet Tandem Tray -

500-Sheet Staple Finisher

Folding Paper Transport Unit

1250-Sheet Staple 2/3 Hole

1250-Sheet Staple 2/4 Hole

2250-Sheet Booklet Staple 2/3

2250-Sheet Booklet Staple 2/4

P/N 57X0225 **Application Solutions** Desktop Contactless Reader 57X0235 Contactless Front Solutions Module (Primary Choice)
Contact Authentication Device 57X0300 57X0301 Contactless Authentication Device 82S1203 IPDS License 82S1204 Bar Code License P/N Connectivity 1021231 Parallel (10') Cable 1021294 USB (2 Meter) Cable RS-232C Serial Interface Card 14F0100 27X0142 Lexmark MarkNet™ N8230 Fiber Ethernet Print Server

37X6146 Fax Card Option 57X7040 English Keyboard Kit SPD0002 Surge Protective Device, 220-240V

P/N Furniture 20L8806 Cabinet 20L8807 Keyboard Shelf

You can install one 1,500-Sheet high-capacity tray, but you must install one 2x550-Sheet tray or one 2,000-Sheet tandem tray beside it.

You can install one 500-Sheet staple finisher, one Offset stacker or one Folding paper transport unit.

You can install one 1,250-Sheet staple hole punch finisher or one 2,250-Sheet booklet staple hole punch finisher, but you must also install a Paper transport unit or Folding paper transport unit, one 550-Sheet tray, and one 2x550-Sheet tray or one 2,000-Sheet tandem tray or one Cabinet.

| Product Specifications                                  | Lexmark CX951se  |  |  |  |  |
|---|--|--|--|--|--|
| Printing  |  |  |  |  |  |
| Display   | Lexmark e-Task 10-inch (25 cm) class colour touch screen   |  |  |  |  |
| Print Speed   | Up to: Black: 35 ppm 1 (A4) / Colour: 35 ppm 1 (A4)  |  |  |  |  |
| Time to First Page                                      | as fast as: Black: TBD seconds / Colour: TBD seconds   |  |  |  |  |
| Print Resolution  | Black: 1200 x 1200 dpi, 4800 Colour Quality / Colour: 4800 Colour Quality, 1200 x 1200 dpi   |  |  |  |  |
| Memory  | Standard: 4 GB / Maximum: 4 GB   |  |  |  |  |
| Hard Disk   | Intelligent Storage Drive included; Magnetic Hard Disk available   |  |  |  |  |
| Recommended Monthly Page Volume                         | 4,000 - 20,000 pages <sup>2</sup>  |  |  |  |  |
| Maximum Monthly Duty Cycle                              | Up to: 100 000 pages per month <sup>3</sup>  |  |  |  |  |
| Copying   |  |  |  |  |  |
| Copy Speed  | Up to: Black: 35 cpm <sup>1</sup> (A4) / Colour: 35 cpm <sup>1</sup> (A4)  |  |  |  |  |
| Time to First Copy                                      | as fast as: Black: TBD seconds / Colour: TBD seconds   |  |  |  |  |
| Scanning  |  |  |  |  |  |
| Scanner Type / ADF Scan                                 | Flatbed scanner with automatic document feeder / DADF (single pass Duplex)   |  |  |  |  |
| A4/Ltr Duplex Scan Speed / Duplex<br>Scan Speed (A4/Ltr | Up to: Black: 200/200 sides per minute / Colour): 200/200 sides per minute   |  |  |  |  |
| A4/Ltr Simplex Scan Speed / Scan<br>Speed (A4/Ltr       | Up to: Black: 100/100 sides per minute / Colour): 100/100 sides per minute   |  |  |  |  |
| ADF Paper Input Capacity                                | Up to: 200 pages 75 gsm bond   |  |  |  |  |
| Supplies 4  |  |  |  |  |  |
| Laser Cartridge Yields                                  | up to: 46,900 <sup>5</sup> -page Colour (CMY) Cartridges / up to: 47,700 <sup>5</sup> -page Black Cartridge  |  |  |  |  |
| Imaging Unit Estimated Yield                            | Up to: 225,000 (black) and 250,000 (colour) pages, based on 3 average letter/A4-size pages per print job and ~ 5% coverage   |  |  |  |  |
| Cartridge(s) Shipping with Product                      | 5,000 <sup>5</sup> -page Black and Color (CMYK) Toner Cartridges <sup>5</sup>  |  |  |  |  |
| Paper Handling  |  |  |  |  |  |
| Included Paper Handling                                 | 500-Sheet Output Bin, 550-Sheet Tray, 150-Sheet Multipurpose Feeder  |  |  |  |  |
| Optional Paper Handling                                 | 2,250-Sheet Booklet Staple Hole Punch Finisher, 500-Sheet Staple Offset Finisher, Folding Paper Transport Unit, 1,250-Sheet Staple Hole Punch Finisher, Offset Stacker, 1,500-Sheet High-Capacity Tray, Paper Transport Unit, 2000-Sheet Tray, Cabinet, 2 x 550-Sheet Tray, 550-Sheet Tray |  |  |  |  |
| Paper Input Capacity                                    | Up to: Standard: 700 pages 75 gsm bond / Maximum: 4750 pages 75 gsm bond   |  |  |  |  |
| Paper Output Capacity                                   | Up to: Standard: 500 pages 75 gsm bond / Maximum: 2650 pages 75 gsm bond   |  |  |  |  |
| Media Types Supported                                   | Vinyl Labels, Labels, Card Stock, Plain Paper, Envelopes, Glossy paper, Refer to the Paper & Specialty Media Guide   |  |  |  |  |
| Media Sizes Supported                                   | A6, Oficio, 304.8 x 483 mm, 7 3/4 Envelope, JIS-B4, 9 Envelope, JIS-B5, A3, Ledger, A4, Legal, SRA3, A5, Hagaki Card, Letter, B5<br>Envelope, C4 Envelope, Statement, C5 Envelope, Executive, DL Envelope, Folio, 10 Envelope  |  |  |  |  |
| General Information                                     |  |  |  |  |  |
| Standard Ports  | Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A), 802.11a/b/g/n/ac + Apple iBeacon, USB 2.0 Specification Hi-Speed Certified (Type B)  |  |  |  |  |
| Optional Network Ports / Optional<br>Local Ports        | MarkNet N8230 Fiber Ethernet Print Server / Internal 1284-B Bidirectional Parallel, Internal RS-232C serial  |  |  |  |  |
| Noise Level   | Operating: TBD dBA (Print) / TBD dBA (Copy) / TBD dBA (Scan)   |  |  |  |  |
| Specified Operating Environment                         | Altitude: 0 - 2896 metres / Humidity: 15 to 80% Relative Humidity / Temperature: 10 to 32.2°C (50 to 90°F)   |  |  |  |  |
| Product Warranty  | 1-Year Onsite Repair, Next Business Day  |  |  |  |  |
| Size / Weight   | H x W x D: 809 x 592 x 660 mm / TBD kg   |  |  |  |  |
| ENERGY STAR Typical Electricity<br>Consumption          | TEC: TBD kilowatt-hours per week   |  |  |  |  |

All information is subject to change without notice. Lexmark is not liable for any errors or omissions.

1 Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.

This is a Class A device according to international electromagnetic emissions standards (i.e. FCC Rules, EN 55022/EN 55032, etc.). Class A products are intended for use in non-residential/non-domestic environments. Use of a Class A product in residential/domestic environments may cause interference to radio communications and require corrective measures.

 $\hbox{@\,}2024$  Lexmark. All rights reserved.

Lexmark, the Lexmark logo and Unison are trademarks of Lexmark International, Inc., registered in the United States and/or other countries.

Apple and AirPrint are trademarks of Apple Inc., registered in the U.S. and other countries. MOPRIA®, the Mopria® Logo™ and the Mopria® Alliance logos are registered trademarks and service marks of Mopria Alliance, Inc. in the United States and other countries. Unauthorised use is strictly prohibited. ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency. EPEAT® is a trademark of the Green Electronics Council in the United States and other countries. All other trademarks are the property of their respective owners.

This product includes software developed by the OpenSSL Project for use in the Open SSL Toolkit (http://www.openssl.org/).



<sup>&</sup>lt;sup>2</sup> "Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage. <sup>3</sup> "Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs. <sup>4</sup> Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/regions for more details. <sup>5</sup> Average continuous black or continuous composite CMY declared cartridge yield up to this number of standard pages in accordance with ISO/IEC 19798.