



Lexmark CX961se

Versatile. Simple. Sustainable.





TONER

Lexmark CX961se

With the new CX961se color A3 multifunction printer, you get reassuring versatility, exceptional sustainability, and surprising simplicity from such sophisticated technology. Boost your productivity with vivid prints — up to 35 pages per minute*. Intuitively navigate the 10-inch (25 cm) color touchscreen, and save time with single-pass two-sided scanning. Effortlessly create everything your business requires, and custom configure your multifunction printer with interchangeable options tailored to your needs.

Versatile: Easy to Use

Create everything your business requires and anything you can imagine — from standard office documents to marketing brochures, booklets and posters — with broad media size support, high-volume printing, and exceptional paper handling and finishing capabilities.

Print vivid, colorful visualizations, charts and documents with professional color features (including PANTONE® calibration) and a full range of media sizes so you can effectively communicate your ideas.

Easily incorporate your multifunction printer into your workspace with a versatile, configurable design that saves space without sacrificing performance.

Boost your productivity with our rich suite of cutting-edge software and solutions with broad capabilities including scanning paper files directly into your cloud-based storage systems and automatically translating documents into 100+ languages.

Further your organization's digital transformation with direct integration into your critical workflows and core business systems using these IoT-enabled devices.



Simple: Easy to Manage

Quickly do what you need to do using an intuitive operator panel and easy-to-follow navigation.

Easily maintain your devices with one-handed toner replacement, easy-to-reach serviceable areas, and alerts that are simple to understand.

Enjoy the peace of mind of knowing you are protected by the industry's most comprehensive security portfolio, right out of the box.

Keep your business running with exceptional reliability, industryleading durability, and long-lasting toner and supplies.

Rest easy that every aspect of your device is made to work together seamlessly thanks to Lexmark's core technology ownership.

Sustainable: Easy to feel good about

Feel good about your purchase and help meet your own sustainability goals with our world-class practices and independent third-party certifications.

Do your part for the planet with our industry-leading use of post-consumer recycled materials and our award-winning cartridge recycling program.

Save energy — and money — with technology that exceeds strict global standards for energy efficiency.

Minimize your impact on the environment with a company that focuses on sustainability throughout the product lifecycle from design through use, end of life and beyond.

This is a Class A device according to international electromagnetic emissions standards (i.e. FCC Rules, EN 55022/EN 55032, etc.). Class A products are intended for use in non-residential/nondomestic environments. Use of a Class A product in residential/domestic environments may cause interference to radio communications and require corrective measures.

* Print speeds measured in accordance with ISO/IEC 24734 (ESAT). For more information see: www.lexmark.com/ISOspeeds.

** Fax icon shown on the operator panel when Fax Server is enabled, Fax Over IP is configured, etherFAX is configured, or an optional Analog Modem is installed.

Lexmark CX961se

LEXI	IIUIK CA9013e		
¢		12	
1	Multifunction product with 10-inch (25 cm) touch screen 858 x 592 x 660 mm 33.8 x 23.3 x 26.0 in.	10	Paper Transport Unit 143 x 412 x 466 mm 5.6 x 16.2 x 18.3 in.
2	500-Sheet output bin Dimensions included as part of base model	11	Folding Paper Transport Unit 184 x 612 x 555 mm 7.2 x 24.1 x 21.9 in.
3	150-Sheet multipurpose feeder Dimensions included as part of base model	12	500-Sheet Staple Finisher 150 x 546 x 523 mm 5.9 x 21.5 x 20.6 in.
4	550-Sheet tray Dimensions included as part of base model	13	Offset Stacker 107 x 420 x 489 mm
5	550-Sheet Tray 163 x 587 x 649 mm	14	4.2 x 16.5 x 19.3 in. 1250-Sheet Staple 2/3 Hole Punch
6	6.4 x 23.1 x 25.6 in. 2 x 550-Sheet Tray 314 x 587 x 649 mm 12.4 x 23.1 x 25.6 in.	14	Finisher 995 x 575 x 610 mm 39.2 x 22.6 x 24.0 in.
7	2000-Sheet Tandem Tray - Letter 314 x 587 x 649 mm 12.4 x 23.1 x 25.6 in.	15	2250-Sheet Booklet Staple 2/3 Hole Punch Finisher 995 x 650 x 613 mm 39.2 x 25.6 x 24.1 in.
8	Cabinet 247 x 587 x 660 mm 9.7 x 23.1 x 26.0 in.		Standard
9	1500-Sheet High-Capacity Tray 290 x 342 x 545 mm 11.4 x 13.5 x 21.4 in.		Optional

<mark>P/N</mark> 20L8200	Hardware Lexmark CX961se
P/N 20L7500 25A0013 77L0H10	Supplies Staple Cartridges (4-pack) Staple Cartridges (3 pack) Lexmark MX953, CS963, CX961, 962, 963, XC9635, 9645, 9655
77L0H20	Black 47.7K Toner Cartridge Lexmark CS963, CX961, 962, 963, XC9635, 9645, 9655 Cyan 46.9K
77L0H30	Toner Cartridge Lexmark CS963, CX961, 962, 963, XC9635, 9645, 9655 Magenta
77L0H40	46.9K Toner Cartridge Lexmark CS963, CX961, 962, 963, XC9635, 9645, 9655 Yellow 46.9K Toner Cartridge
77L0W00	Lexmark CS963, CX950, 951, 961, 962, 963, 833, XC9525, 9535, 9635, 9645, 9655, 8355 120K
77L0Z10	Waste Container Lexmark MX953, CS963, CX950, 951, 961, 962, 963, 833, XC9525, 9535, 9635, 9645, 9655, 8355
77L0Z50	Black 225K Imaging Unit Lexmark CS963, CX950, 951, 961, 962, 963, 833, XC9525, 9535, 9635, 9645, 9655, 8355 3-Color
77LOZKO	250K Imaging Kit Lexmark MX953, CS963, CX950, 951, 961, 962, 963, 833, XC9525, 9535, 9635, 9645, 9655, 8355
77LOZVO	Black Return Programme 225K Imaging Unit Lexmark CS963, CX950, 951, 961, 962, 963, 833, XC9525, 9535, 9635,9645, 9655, 8355 3-Color Return Programme 250K Imaging
77L10C0	Kit Lexmark CS963, CX950, 951, 961, 962, 963, 833 Cyan Return
77L10K0	Programme 12K Toner Cartridge Lexmark MX953, CS963, CX950, 951, 961, 962, 963, 833 Black Return Programme 15K Toner
77L10M0	Cartridge Lexmark CS963, CX950, 951, 961, 962, 963, 833 Magenta Return
77L10Y0	Programme 12K Toner Cartridge Lexmark CS963, CX950, 951, 961, 962, 963, 833 Yellow Return
77L1HC0	Programme 12K Toner Cartridge Lexmark CS963, CX961, 962, 963 Cyan Return Programme 46.9K
77L1HKO	Toner Cartridge Lexmark MX953, CS963, CX961, 962, 963 Black Return Programme 47.7K Toner
77L1HM0	Cartridge Lexmark CS963, CX961, 962, 963 Magenta Return Programme
77L1HY0	46.9K Toner Cartridge Lexmark CS963, CX961, 962, 963 Yellow Return Programme 46.9K Toner Cartridge
P/N 20L8800 20L8801 20L8802 20L8803	Paper Handling 550-Sheet Tray 2 x 550-Sheet Tray 2,000-Sheet Tandem Tray – A4 2,000-Sheet Tandem Tray – Letter

20L8800	550-Sheet Tray
20L8801	2 x 550-Sheet Tray
20L8802	2,000-Sheet Tandem Tray – A4
20L8803	2,000-Sheet Tandem Tray –
	Letter
20L8804	1,500-Sheet High-Capacity Tray
20L8810	500-Sheet Staple Finisher
20L8811	Folding Paper Transport Unit
20L8812	1250-Sheet Staple 2/3 Hole
	Punch Finisher
20L8813	1250-Sheet Staple 2/4 Hole
	Punch Finisher

20L8814 20L8815 20L8816	2250-Sheet Booklet Staple 2/3 Hole Punch Finisher 2250-Sheet Booklet Staple 2/4 Hole Punch Finisher Offset Stacker
20L8817	Paper Transport Unit
P/N 27X0420	Memory Options 500GB Hard Disk Drive (SATA)
P/N 57X0225 57X0235 57X0300 57X0301 82S1203	Application Solutions Desktop Contactless Reader Contactless Front Solutions Module (Primary) Contact Authentication Device Contactless Authentication Device IPDS License
82\$1204	Bar Code License
P/N 1021231 1021294 14F0100 27X0142 37X6146 57X7040 SPD0001	Connectivity Parallel (10') Cable USB (2 Meter) Cable RS-232C Serial Interface Card Lexmark MarkNet™ N8230 Fiber Ethernet Print Server Fax Card Option English Keyboard Kit Surge Protective Device, 110-120V
P/N 20L8806	Furniture Cabinet

Keyboard Shelf

20L8806 20L8807

You can install one 550-Sheet tray.

You can install one 2x550-Sheet tray, one 2,000-Sheet tandem tray or one Cabinet, but you must also install one 550-Sheet tray above it.

You can install one 1,500-Sheet high-capacity tray, but you must install one 2x550-Sheet tray or one 2,000-Sheet tandem tray beside it.

You can install one 500-Sheet staple finisher, one Offset stacker or one Folding paper transport unit.

You can install one 1,250-Sheet staple hole punch finisher or one 2,250-Sheet booklet staple hole punch finisher, but you must also install a Paper transport unit or Folding paper transport unit, one 550-Sheet tray, and one 2x550-Sheet tray or one 2,000-Sheet tandem tray or one Cabinet.

Product Specifications	Lexmark CX961se
Printing	
Display	Lexmark e-Task 10-inch (25 cm) class colour touch screen
Print Speed	Up to: Black: 35 ppm ¹ (Letter) / Colour: 35 ppm ¹ (Letter)
Time to First Page	as fast as: Black: 71 seconds / Colour: 8.2 seconds
Print Resolution	Black: 1200 x 1200 dpi, 4800 Color Quality / Colour: 4800 Color Quality, 1200 x 1200 dpi
Memory	Standard: 4 GB / Maximum: 4 GB
Hard Disk	Intelligent Storage Drive included; Magnetic Hard Disk available
Recommended Monthly Page Volume	4,000 - 20,000 pages ²
Maximum Monthly Duty Cycle	Up to: 150 000 pages per month ³
Copying	eb to too bege be moral.
Copy Speed	Up to: Black: 35 cpm ¹ (Letter) / Colour: 35 cpm ¹ (Letter)
Time to First Copy	as fast as: Black: 8.5 seconds / Colour: 9.5 seconds
Scanning	
Scanner Type / ADF Scan	Flatbed scanner with automatic document feeder / DADF (single pass Duplex)
A4/Ltr Duplex Scan Speed	Up to: Black: 240/240 sides per minute / Colour: 240/240 sides per minute
A4/Ltr Simplex Scan Speed	Up to: Black: 120/120 sides per minute / Colour: 120/120 sides per minute
ADF Paper Input Capacity	
Supplies ⁴	Up to: 300 pages 20 lb or 75 gsm bond
	un to 4/ 2005 a new Colour (CNN) Contriduce / un to 47700 5 mere Plath Contriduc
Laser Cartridge Yields	up to: 46,900 ⁵ -page Colour (CMY) Cartridges / up to: 47,700 ⁵ -page Black Cartridge
Imaging Unit Estimated Yield	Up to: 225,000 (black) and 250,000 (colour) pages, based on 3 average letter/A4-size pages per print job and ~ 5% coverage
Cartridge(s) Shipping with Product	15,000 ⁵ -page Black Toner Cartridge ⁵ , 12,000 ⁵ -page Colour (CMY) Toner Cartridges ⁵
Paper Handling	
Included Paper Handling	500-Sheet Output Bin, 550-Sheet Tray, 150-Sheet Multipurpose Feeder
Optional Paper Handling	2,250-Sheet Booklet Staple Hole Punch Finisher, 500-Sheet Staple Offset Finisher, Folding Paper Transport Unit, 1,250-Sheet Staple Hole Punch Finisher, Offset Stacker, 1,500-Sheet High-Capacity Tray, Paper Transport Unit, 2000-Sheet Tandem Tray, Cabinet, 2 x 550-Sheet Tray, 550-Sheet Tray
Paper Input Capacity	Up to: Standard: 700 pages 20 lb or 75 gsm bond / Maximum: 4750 pages 20 lb or 75 gsm bond
Paper Output Capacity	Up to: Standard: 500 pages 20 lb or 75 gsm bond / Maximum: 2650 pages 20 lb or 75 gsm bond
Media Types Supported	Vinyl Labels, Labels, Card Stock, Plain Paper, Envelopes, Glossy paper, Refer to the Paper & Specialty Media Guide
Media Sizes Supported	A6, Oficio, 12 x 18", 7 3/4 Envelope, JIS-B4, 9 Envelope, JIS-B5, A3, Ledger, A4, Legal, SRA3, A5, Hagaki Card, Letter, B5 Envelope, C4 Envelope, Statement, C5 Envelope, Executive, DL Envelope, Folio, 10 Envelope
General Information	
Standard Ports	Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A), 802.11a/b/g/n/ac + Apple iBeacon, USB 2.0 Specification Hi-Speed Certified (Type B)
Optional Network Ports / Optional Local Ports	MarkNet N8230 Fiber Ethernet Print Server / Internal 1284-B Bidirectional Parallel, Internal RS-232C serial
Noise Level	Operating: 46 dBA (Print) / 52 dBA (Copy) / 50 dBA (Scan)
Specified Operating Environment	Altitude: 0 - 2896 Meters (9,500 Feet) / Humidity: 15 to 80% Relative Humidity / Temperature: 10 to 32.2°C (50 to 90°F)
Limited Warranty	See Statement of Limited Warranty: 1-Year Onsite Repair, Next Business Day
Size / Weight	H x W x D: 858 x 592 x 660 mm / 90.1 kg
ENERGY STAR Typical Electricity Consumption	TEC: 0.58 kilowatt-hours per week

All information is subject to change without notice. Lexmark is not liable for any errors or omissions.

¹ Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds. ² "Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage. ³ "Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs. ⁴ Product functions only with replacement cartridge signed for use in a specific geographical region. See www.lexmark.com/regions for more details. ⁵ Average continuous black or continuous composite CMY declared cartridge yield up to this number of standard pages in accordance with ISO/IEC 19798.

This is a Class A device according to international electromagnetic emissions standards (i.e. FCC Rules, EN 55022/EN 55032, etc.). Class A products are intended for use in non-residential/nondomestic environments. Use of a Class A product in residential/domestic environments may cause interference to radio communications and require corrective measures.

© 2024 Lexmark. All rights reserved.

lexmark.ca

Lexmark, the Lexmark logo and Unison are trademarks of Lexmark International, Inc., registered in the United States and/or other countries.

Apple and AirPrint are trademarks of Apple Inc., registered in the U.S. and other countries. MOPRIA®, the Mopria® Logo™ and the Mopria® Alliance logos are registered trademarks and service marks of Mopria Alliance, Inc. in the United States and other countries. Unauthorized use is strictly prohibited. ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency. EPEAT® is a trademark of the Green Electronics Council in the United States and other countries. All other trademarks are the property of their respective owners.

This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (http://www.openssl.org/).